

CHAINS

Page 16.

T4SR9W (cont)

Witnesses: B. Sheehan
W. Johnson
M. Whitmore
R. Long

by Leonard Whitmore,
Tillamook co. deputy surveyor
3-4-61

T4SR9W

$\frac{1}{4}$ $\frac{8}{17}$ $\frac{1}{4}$ corner to sections 8-17
Original Monument:
Alder post in a mound of stone.

Original Witnesses:
5" fir, N.4°30'W., 244Lks Mkd. $\frac{1}{4}$ S8BT
No BTs Mkd in section 17

I found a rock mound with a stone marked $\frac{1}{4}$ S8 on North
and $\frac{1}{4}$ S17 on South faces. I found a 30" fir, N.4°30'W., 161ft.
with a healed witness face. A road may destroy the orig.
NW BT.

I marked 2 new BTs:
26" fir, N.22°30'W., 7ft. Mkd. $\frac{1}{4}$ S8BT
14" fir, S.38°30'W., 23ft. Mkd. $\frac{1}{4}$ S17BT

Witness: M. Whitmore
by Leonard Whitmore,
Tillamook Co. deputy surveyor
2-22-61

16 | 15

T4SR9W

$\frac{1}{4}$ Original Monument
14x10x8 basaltic rock Mkd. $\frac{1}{4}$ S15 on E. and $\frac{1}{4}$ S16
on W. sides. in a rock mound. No trees were
marked for witnesses.

I found a man made rock mound on a steep west slope.
Found the marked stone with visible S16 where it had rolled
fifty feet down the slope ^{TO A BENCH} ~~at the stone mound.~~
I REPLACE THE MARKED STONE AT THE STONE MOUND

I marked 2 new BTs:
28" fir, N.26°30'E., 37ft. Mkd. $\frac{1}{4}$ S15BT
18" fir, S.6°30'W., 18 $\frac{1}{2}$ ft. Mkd $\frac{1}{4}$ S16BT

Witness: M. Whitmore
By Leonard Whitmore,
Tillamook Co. deputy surveyor
2-22-61