

CHAINS

Page 17.

T4SR9W

$\frac{1}{4}$ $\frac{16}{21}$

$\frac{1}{4}$ Corner to sections 16-21

Original Monument:

Fir post with a marked basaltic rock 12x10x10

Mkd. $\frac{1}{4}$ S16 on N. and $\frac{1}{4}$ S21 on S. face in a rock mound.

Original Witness:

8" fir, N.48°30'E., 281 Lks. Mkd. $\frac{1}{4}$ S21BT

No witness was marked for section 16.

I found the original post still standing with visible Mks.

$\frac{1}{4}$ S16 on N. side. Found a rock mound built around the post with

a rock marked $\frac{1}{4}$ S16. Found 48" fir, N.48°30'E., 185 $\frac{1}{2}$ ft. with

a healed witness face.

I marked one BT:

16" fir, S.63°30'W., 46 $\frac{1}{2}$ ft. Mkd. $\frac{1}{4}$ S21BT

Witness: M. Whitmore

by Leonard Whitmore,

Tillamook Co. deputy surveyor

2-22-61

T4SR9W

$\frac{1}{4}$ $\frac{14}{23}$

Original Monument:

Cedar post Mkd. $\frac{1}{4}$ S14 on N. and $\frac{1}{4}$ S23 on S. sides.

Original Witnesses:

30" snag, S.40°30'E., 67Lks. Mkd. $\frac{1}{4}$ S23BT

40" snag, N.28°E., 55Lks. Mkd. $\frac{1}{4}$ S14BT

I found the original cedar post lying upon the ground with a visible mark "4". A rock mound is at the base of the post. I found a 30" snag, S.40°30'E., 67Lks. with marks rotted off. Found a 40" snag, N.28°E., 55Lks. with Mks. rotted off. I set 1 $\frac{1}{2}$ " pipe and wire the original post to pipe.

I marked 2 new BTs:

20" hem., S.33°W., 9ft. Mkd. $\frac{1}{4}$ S23BT

12" fir, N.50°W., 22 $\frac{1}{2}$ ft. Mkd. $\frac{1}{4}$ S14BT

This corner is approx. $\frac{1}{4}$ mile east of the Mt Hebo

Radar base.