

Resurvey of Portion of North Boundary of

125

T. 3 S., R. 10 W.

Chains.	
18.80	Ravine, course S., asc. 41 ft. over E. slope.
20.70	Spur, slopes SW.
22.20	Desc. 106 ft. over W. slope, along old trail, and edge of old burn.
27.81	Point for $\frac{1}{4}$ sec. cor. of sec. 4 only, determined as hereinafter set forth.
29.64	Creek, 4 lks. wide, course S., asc. 124 ft. over E. slope.
36.00	Spur, slopes S., over rolling land.
37.45	Creek, 1 lk. wide, course S.
38.55	Point for $\frac{1}{4}$ sec. cor. of sec. 33 only, as determined by record bearing and distance from original SE. bearing tree.
	At point for $\frac{1}{4}$ sec. cor.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 33 only, with brass cap mkd.
	$\frac{1}{4}$ S 33
	1933
	from which
	A hemlock, 36 ins. diam., bears S. 26° E., 39 lks. dist., mkd. $\frac{1}{4}$ S B T. (Old B. T.)
	A hemlock, 14 ins. diam., bears N. 82° E., 157 lks. dist., mkd. $\frac{1}{4}$ S 33 B T. (New B. T.)
	A hemlock, 7 ins. diam., bears N. 72° W., 46 lks. dist., mkd. $\frac{1}{4}$ S 33 B T. (New B. T.)
	Thence
	S. 89° 03' W., on true line on south bdy. of sec. 33, with new measurement.
	Asc. 82 ft. over E. slope.
4.80	Spur, slopes S., desc. 126 ft. over W. slope.
11.50	Creek, 4 lks. wide, course SW.
13.80	Creek, 3 lks. wide, course S. 20° E., over rolling land.
16.50	Creek, 1 lk. wide, course S., asc. 112 ft. over E. slope.
25.90	Spur, slopes SE., desc. 15 ft. over SW. slope.
26.00	Point for closing cor. of secs. 4 and 5, determined as hereinafter set forth.
27.00	Creek, 5 lks. wide, course SE., asc. 310 ft. over NE. slope.
35.00	Creek, 1 lk. wide, 20 lks. N. of line, course N. 80° E. Slope changes to E.
39.66	Point for cor. of secs. 32 and 33 only, determined at record distances from both original bearing trees.

BOOK 3