

Resurvey of Portion of North boundary of

T. 3 S., R. 10 W.

Chains	
39.94	<p>The $\frac{1}{4}$ sec. cor. of sec. 31 only, which is a stake, 3 sq., 30 ins. above ground, mkd. $\frac{1}{4}$ S.</p> <p>At point for $\frac{1}{4}$ sec. cor.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 31 only, with brass cap mkd.</p> <p style="text-align: center;"><u>$\frac{1}{4}$ S31</u> 1933</p> <p style="text-align: right;">from which</p> <p>A hemlock, 24 ins. diam., bears S. 69° W., (not S. 62° W.) 18 lks. dist., marks grown over. (Old B. T.)</p> <p>A stump, bears N. 48° W., 30 lks. dist. (Old B. T.)</p> <p>A hemlock, 30 ins. diam., bears N. 42° E., 81 lks dist., mkd. $\frac{1}{4}$ S 31 B T. (New B. T.)</p> <p>A hemlock, 30 ins. diam., bears N. 68° W., 55 lks dist., mkd. $\frac{1}{4}$ S 31 B T. (New B. T.)</p>
	<p>Thence</p> <p>S. 89° 26' W., with new measurement, on true line on sou bdy. of sec. 31.</p> <p>Desc. 324 ft. over NW. slope.</p>
16.94	<p>Sand Lake Trail, bears NE. and SW.</p>
21.75	<p>Creek, 10 lks. wide, course SW., asc. 64 ft. over SE. slope.</p>
27.50	<p>Spur, slopes S., desc. 136 ft. over SW. slope.</p>
39.90	<p>Point for the cor. of Tps. 2 S., Rs. 10 and 11 W., as determined by reference to the record bearing and distance to the original NE., SE., and SW., bearing trees, and record distance from the original NW. bearing tree.</p>
	<p>At point for cor.</p> <p>Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for cor. of Tps. 2 S., Rs. 10 and 11 W. with brass cap mkd.</p>
	<p style="text-align: center;">T2S R11W R10W <u>S36 S31</u> T3S R11W S1 1933</p> <p style="text-align: right;">from which</p>
	<p>A stump, bears N. 50° E., 45 lks. dist. (Old B. T.)</p>
	<p>A stump, bears S. 21$\frac{1}{2}$° E., 29 lks. dist. (Old B. T.)</p>
	<p>A snag, 65 ins. diam., bears S. 62$\frac{1}{2}$° W., 53 lks. dist., mkd. S 1 B T. (Old B. T.) - I obliterate the marks on this tree.</p>