

Dependent Resurvey of Portion of West Boundary of
T. 3 S., R. 10 W.

Chains.	
	North, record bearing, on true line bet. secs. 1 and 2. Over rolling land, through heavy timber and dense undergrowth.
4.57	Creek, 2 lks. wide, course SW., asc. 162 ft. over SE. slope.
14.50	Spur, slopes E., over rolling land.
20.00	Record dist., set an iron post, 3 ft. long, 1 in. dia 27 ins. in the ground for S 1/16 sec. cor., with brass cap mkd. S 1/16 S 1 S 6 1933 from which A hemlock, 11 ins. diam., bears S. 48° E., 29 lks. dist., mkd. S 1/16 S 6 B T. A hemlock, 10 ins. diam., bears N. 50° W., 10 lks. dist., mkd. S 1/16 S 1 B T.
21.30	Creek, 2 lks. wide, course SE., asc. 546 ft. over SW. slope.
38.82	Sand Lake Trail, bears E. and W.
40.00	Record dist., set an iron post, 3 ft. long, 1 in. dia 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd. 1/4 S 1 S 6 1933 from which A hemlock, 30 ins. diam., bears S. 25° E., 12 lks. dist., mkd. 1/4 S 6 B T. A hemlock, 25 ins. diam., bears S. 60° W., 21 lks. dist., mkd. 1/4 S 1 B T. This cor. is on top of ridge, bears E. and W.
Dependent Resurvey of Portion of Subdivisional Lines T. 3 S., R. 10 W.	

"Reestablishment of the survey executed by Albert P. Wilson, U. S. Deputy Surveyor, in 1890," Retracement.	
	From the cor. of secs. 3, 4, 9, and 10.
	North, retracing bet. secs. 3 and 4.
40.00	Find no trace of 1/4 sec. cor.
84.98	Fall 520 lks. E. of old closing cor. of secs. 3 and 4.
85.13	Intersect S. bdy. of sec. 34, T. 2 S., R. 10 W., at