

County Surveyor's Record, Tillamook County, Oregon

PAGE 8

TOWNSHIP ~~8~~ NORTH, RANGE 9 WEST

NE 1/16 CORNER, SECTION 6, T1N, R9W

DROVE 1/2" IRON PIPE FOR THE CORNER; ESTABLISHED BY L.F.CO.

REFERENCED THE FOLLOWING:

17" HEMLOCK BEARS N 18°W 2.9 FT. "NE 1/16 S6"
12" FIR BEARS N 36°E 21.5 FT. "NE 1/16 S6"

5

CORNER IS 115 FT. SOUTH OF CREEK, COURSE WEST.

CORNER IS ON ROCKY POINT 75 FT. EAST OF SLIDE AREA, 200 FT. BELOW TOP OF RIDGE.

VAR. 21°30'
JULY 19, 1962

REFERENCED BY: W. JORDAN, LFCO.
WITNESS: R. STEWART

C-N 1/16 CORNER, SECTION 6, T1N, R9W

DROVE 1/2" X 30" IRON PIPE FOR CORNER; ESTABLISHED BY L.F.CO.

REFERENCED THE FOLLOWING:

12" HEMLOCK BEARS S 72°W 3.5 FT. "CN 1/16 S6"
62" SPRUCE BEARS N 62°W 31.2 FT. "CN 1/16 S6"

5

CORNER IS 150 FT. NORTH OF CREEK.

VAR. 21°30'
JULY 20, 1962

REFERENCED BY: W. JORDAN, LFCO.
WITNESS: R. STEWART

1/4 CORNER, SECTIONS $\frac{6}{7}$, T1N, R9W

CORNER RESTORED BY PROPORTIONATE MEASUREMENT BY L.F. Co.

SET 3/4" X 36" PIPE ON VERY STEEP NORTH SLOPE APPROXIMATELY 1 TALLY SOUTH OF CREEK, COURSE WEST.

4

SCRIBED THE FOLLOWING B.T.'S.:

12" FIR BEARS N 16°E 11.35 FT. "1/4 S6" S. NAIL, L. WASHER, Y. TAG
9" FIR BEARS N 74°W 13.00 FT. "1/4 S6" S. NAIL, L. WASHER, Y. TAG

JULY 12, 1967

SCRIBED BY: W. BREWER, LFCO.
WITNESSES: R. BASS, R. MCCOLLAM

BOOK 3

BOOK 3