

County Surveyor's Record, Tillamook County, Oregon

PAGE 6

TOWNSHIP 5 SOUTH, RANGE 10 WEST

E 1/16 CORNER ON TOWNSHIP LINE, SECTION 34, T5S, R10W

SET 1 1/2" STAINLESS STEEL PIPE.

5

SCRIBED THE FOLLOWING B.T.'S:

23" SPRUCE BEARS S 78° W 21.0 FT. Y. TAG

26" HEMLOCK BEARS S 29° E 14.7 FT. Y. TAG

CORNER SETS 60 FT. NORTH OF GENTLE SPUR RIDGE, AND 100 FT. SOUTH OF SMALL CREEK FLOWING WEST.

MAY 8, 1967

SET BY: R. STEWART
WITNESSES: R. ENGLAND, D. WILLIAMS

STANDARD CORNER, SECTIONS 34/35, T5S, R10W

SET 2" IRON PIPE BESIDE ORIGINAL STONE AT STANDARD CORNER SEC. 34/35.

JANUARY, 1967

SET BY: R. STEWART
WITNESSES: R. ENGLAND, D. WILLIAMS

STANDARD 1/4 CORNER, SECTION 34, T5S, R10W

FOUND 2 PIPES, 1 WITH BRASS CAP AND 3 B.T.'S WITH TAGS.

CORNER IS 113 FT. EAST OF CREEK, COURSE S.W.

JANUARY, 1967

FOUND BY: R. STEWART
WITNESSES: R. ENGLAND, D. WILLIAMS

STANDARD CORNER, SECTIONS 33/34, T5S, R10W

FOUND IRON PIPE AND PIPE WITH BRASS CAP FOR STANDARD CORNER.

CORNER SETS IN SMALL DRAW BEARING NORTH AND SOUTH.

CORNER IS APPROXIMATELY 5 CHAINS NORTH OF MAIN RIDGE BEARING EAST AND WEST AND 1 CHAIN SOUTH OF CREEK FLOWING WEST.

3 B.T.'S WITH TAGS.

JANUARY, 1967

FOUND BY: R. STEWART
WITNESSES: R. ENGLAND, D. WILLIAMS

BOOK 3