

County Surveyor's Record, Tillamook County, Oregon

383

1/4 S 11/14
1969
PE 2301
ORE

From which I scribed:

- a 24 in. spruce bears N 67° E, 21.8 ft., mkd. S 1/4, S 11, BT
- a 46 in Spruce bears S 5° W, 27.6 ft., mkd. S 1/4, S 14, BT.

Searched diligently, but could not locate any sign of 1905 corner set by County Surveyor.

- 2,670 Begin steep asc. through scattered timber and dense underbrush.
- 3,800 Begin descent into small draw through heavy brush.

3,924.3 Point for E 1/16 cor. Sec. 11/14, T 5 S, R 10 W, in Vine maple patch in small draw.

Set 2x30 in. G.I.P. - 3 in. Brass Cap mkd.

E 1/16 11/14
1969
PE 2301
ORE

From which I scribed:

- a 42 in. Spruce bears N 70° E, 47.0 ft., mkd. E 1/16 S 11 BT.
- a 46 in. Spruce bears S 40° W, 64.5 ft., mkd. E 1/16 S 14 BT.
- an old cor. stake bears S 18° E, 11.7 ft.

- 3,925 Begin rolling asc. through big timber and dense underbrush.
- 4,750 Begin rolling terrain through big timber and little underbrush.
- 5,232.42 Found U.S.F.S. Brass Cap with 3 brg. trees and 1 brg. stump in corner of clear cut bdy. for Sec. corner 11, 12, 13, 14 as described in the official county survey records.

Land generally rolling with dense underbrush.

8/6/69

But W. Udell

R.P.E. 2301