

# County Surveyor's Record, Tillamook County, Oregon

## CHAINS

Rewitness of the 1/4 corner common to Section 32, T1S, R10W and Section 5, T2S, R10W., W.M.

Original corner was set in 1857 by Samuel D. Snowden, "Set post for 1/4 section corner from which bears:

12" Hemlock N 35°W, 28 lks  
8" Spruce S 29E, 27 lks"

Rewitnessed in September 1924 by W. E. Anderson. "Reset 1/4 corner between Sections 5 and 32, T1 and 2S, R10W, from old B.T. Made new BT's:

18" Spruce S 60°E, 21.3 ft.  
20" Hemlock N 85°W, 5.7 ft."

Tillamook County Records Bk 4,  
Page 31

Rewitnessed in August 1956 by C. G. Collard and Jerry Gass "Found Bearing Trees scribed by County Surveyors Anderson and Gustrom in 1924 down at West edge of timber, the timber west of the corner having been logged, with the old corner stake uprooted intact with the earth wad of the closest tree. After estimating the position of the trees when they were standing, I set an iron pipe in the exact location called for in Anderson's notes. This coincided with the estimated original position of the uprooted stake. The iron pipe is 3/4" galvanized pipe, 20" in the ground and 4" above, with 1 1/2" babbited cap, from which I scribed new bearing trees:

12" Hemlock marked 1/4 B.T. #376 bears S 76°E, 58.6 ft.  
16" Hemlock marked 1/4 B.T. #376 bears S 40° 40'E,  
80.2 ft."

On November 7, 1969 I again visited the 1/4 corner and found the iron pipe with cap in its proper location. Both the B.T.'s I had scribed in 1956 were in good condition but recently uprooted. I scribed a new bearing tree as follows:

10" Hemlock marked BT-S5-376 bears S 46°W, 26.4 ft.

*Charles G. Collard*

By: Charles G. Collard  
Registered Land Surveyor  
Oregon #376

Witnesses: G. W. Jaques  
W. T. Williamson

November 7, 1969