


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

(Reference FSH 5681.65)

History of original corner establishment:

Corner was established by the General Land Office in August of 1882.



Description of corner evidence found:

A 3/4 inch iron pipe 36 inches above ground from which

A 4 inch hemlock bears N32E 4.2 feet tag good

A 4 foot high stub bears N82E 12.5 feet (original)


A 6 inch hemlock bears S63E 10.0 feet tag good

A 1 foot high rotted stub bears N64W 10.6 feet with slab mkd sl6 (original)

A 36 inch hemlock bears N67W 12.4 feet-tag good
Description of monument and accessories established to perpetuate the original location of this corner

Set a 2" x 30" iron pipe with brass cap marked

T 3 S R 10 W



1969

650

Set a 3/4" iron pipe along side from which

I scribed a 5" hemlock brs S85E 16.3 ft mkd XBT - tagged

Set a 6' steel post south of corner with F.S. boundary signs facing west. Painted red band on each BT.

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of.....; 19....., at..... o'clock.....m., (signed)

(COUNTY OFFICIAL)

by

(DEPUTY)

REGISTERED OREGON LAND SURVEYOR

Tom O. McCullough

JULY 10, 1964
TOM O. McCULLOUGH
650

BOOK 3

320