


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

corner established in 1904 by Morris Wygant.



Description of corner evidence found:

Found original vine maple post mkd ¼ S7 on west & 8 on east from which

16" hemlock brs. S88W 33.5 ft.
with tag - with visible marks - ¼ S7 BT (orig)

30" hemlock brs. N1W 19.0 ft.
with visible marks - 8 B (orig)

It appears that the bearing and distance have been reversed on the original notes.

Description of monument and accessories established to perpetuate the original location of this corner

Set 2"x30" iron pipe with brass cap mkd

T6S R9W
 ¼ 7 | 8
 1970
 650 from which

18" hemlock brs. S71E 12.4 ft.
scribed ¼ S8 BT 650

Set 2 fence posts with signs ± 5 ft. south facing east
± 5 ft. east facing south

Office of County Surveyor County of Tillamook
 State of OREGON, I hereby certify that the within instrument was filed in this office
 for record on the 15th day of MAY, 1970, at o'clock m. (Signed)
John C. Carter CS by (DEPUTY)
 (COUNTY OFFICIAL)

REGISTERED
 OREGON
 LAND SURVEYOR
 JULY 10, 1964
 TOM O. McCULLOUGH
 650

340