


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1878 by Henry Meldrum.



Description of corner evidence found:

Found 3/4" pipe from which


- 54" fir stump brs. N26E 45.0 ft - with visible T (orig)
- 56" fir snag brs. S20W 28.4 ft - scribing visible (orig)
- 50" fir snag brs. N40W 28.4 ft - no evidence visible (orig)
- 26" hemlock brs. N52W 13.6 ft - with tag - with scribing
- 28" hemlock brs. N29E 12.2 ft - with tag - with scribing
- 30" hemlock brs. S14W 25.0 ft - with tag - face healed

The last three BTs scribed by L. Whitmore in 1963

Description of monument and accessories I established to perpetuate the original location of this corner

Set a 2"x30" iron pipe with brass cap mkd

T4S, R10W



1970
650

Set pipe next to corner

Set fence post with sign + 5 ft to the west facing north.

Office of County Surveyor County of Tillamook
 State of OREGON, I hereby certify that the within instrument was filed in this office
 for record on the 15th day of May, 1970, at o'clockm., (signed)
Marked CS (COUNTY OFFICIAL) by (DEPUTY)

REGISTERED
 OREGON
 LAND SURVEYOR

Tom O. McCullough
 JULY 10, 1964
 TOM O. McCULLOUGH
 650

BOOK 3

355