


CERTIFIED RECORD OF LAND CORNER MONUMENT

History of original corner establishment:

Corner was originally set by Henry Meldrum in 1878. He set a post and scribed an alder 12" in diameter which brs. N18E 356 lks. and A12" fir brs. N18E 106 lks. John Carlich, Tillamook County Surveyor, set a brass cap and scribed spruce and alder BTs in 1970.



Description of corner evidence found:

Found a 2" <sup>1</sup>/<sub>4</sub> iron pipe with brass cap marked

T4S 33 R10W  
4

5S

RS287  
1970

metal post with location poster south 1 foot from which

A 9" alder brs. S77W 21.3 feet - bark scribed (Carlich)

A 36" spruce brs. N30W 49.1 feet - scribing visible (Carlich)

A 56" fir brs. N15E 100 feet - face chopped out, but no scribing

Description of monument and accessories established to perpetuate the original location of this corner

None

Set steel post 2 feet west of brass cap with attention sign facing north. Painted red band on BTs.

Office of COUNTY SURVEYOR County of TILLAMOOK  
State of OREGON, I hereby certify that the within instrument was filed in this office  
for record on the 18 day of SEPTEMBER, 1970, at ..... o'clock .....m., (signed)  
[Signature] by County Surveyor  
(COUNTY OFFICIAL)

REGISTERED  
OREGON  
LAND SURVEYOR

[Signature]  
JULY 17, 1970  
RICHARD L. BRYANT  
920

BOOK 3

Form R6-7100-57 (9/66)

376