


CERTIFIED RECORD OF LAND CORNER MONUMENTS

History of original corner establishment:

Corner set by Charles Branson in 1898. He set a post and stone and scribed a fir and alder B^t
M. Whitmore found the corner in 1961 and scribed a new BT



Description of corner evidence found:

Found stone with 21 on west face and 22 on east face set in mound of stone from which

A 17" fir brs. N35¹/₂E 42.5 feet
face healed (M. Whitmore 2/11/61)


A rotted 18" fir windfall brs. N15E 18 ft
scribing barely visible (orig)

A 22" alder brs. N49¹/₂W 63 ft
face healed (orig)

Standard corner to section 28 brs. east 96.0 ft
Corner marked by a stone and brass cap.

Description of monument and accessories established to perpetuate the original location of this corner

Set 2"x30" iron pipe with brass cap marked



1970
920

Set original stone beside brass cap and piled stone around pipe.
Bark scribed original alder BT as follows: S 21 BT 920

Drove steel fence post 3 feet north of corner with attention sign facing west. Painted red band on BT and placed BT tags.

Office of COUNTY SURVEYOR County of TILLAMOOK
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 9th day of SEPTEMBER, 1970, at o'clock m., (signed)
[Signature] CO. SURVEYOR by
(COUNTY OFFICIAL)

(DEPUTY)
REGISTERED
OREGON
LAND SURVEYOR

[Signature]
JULY 17, 1970
RICHARD L. BRYANT
920