


CERTIFIED RECORD OF LAND CORNER MONUMENTS

History of original corner establishment:

Corner originally set by Henry Meldrum in 1879. M. Whitmore found corner and scribed a BT in 1961.



Description of corner evidence found:


Found a 14"x9"x7" stone with 4 notches on north edge and 3 visible notches on west edge from which

1 1/2" fir brs. S41W 11.5 feet
face healed (M. Whitmore 2/11/61)
Closing corner sections 22 & 27 brs. South 53.5 feet.
Closing corner sections 21 & 22 brs. west 96.0 feet
Both corners marked by stone and brass cap.

Description of monument and accessories established to perpetuate the original location of this corner

Set 2"x30" iron pipe with brass cap marked

T4S R9W



Set stone beside brass cap

Set steel fence post 3 ft south of corner with attention sign facing east.
Painted red band on BT and placed BT tag.

Office of COUNTY SURVEYOR County of Tillamook
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 9th day of SEPTEMBER, 1970, at o'clock m., (signed)
Richard L. Bryant Surveyor by (COUNTY OFFICIAL)

REGISTERED
OREGON
LAND SURVEYOR

BOOK 3

381

Richard L. Bryant

Form R6-7100-57 (9/66)

JULY 17, 1970
RICHARD L. BRYANT
920