


CERTIFIED RECORD OF LAND CORNER MONUMENTS

History of original corner establishment:

Corner originally set by Caudle in 1880. He set stone 12x8x6" and built stone mound as per instructions.



Description of corner evidence found:

Found 12x8x6" stone with X scribed from which

A 37" spruce brs. N63W 58.5 ft  
with pitched face


A 37" split trunk alder brs. S37W 600 ft.  
scribing visible - with OSBF tag

A 32" alder brs. S66E 68.4 ft.  
scribing visible

Description of monument and accessories established to perpetuate the original location of this corner

Set 2"x30" iron pipe with brass cap marked

T3S R9W



1970  
650

Buried stone beneath brass cap  
Built rock mound around brass cap  
Set fence post + 5 ft west with signs facing north

No tree suitable for BT in NE quadrant.

REGISTERED  
OREGON  
LAND SURVEYOR

*William Rust*

JULY 17, 1970  
WILLIAM R. RUST  
936

Office of COUNTY SURVEYOR County of TILLAMOOK  
State of OREGON, I hereby certify that the within instrument was filed in this office  
for record on the 9 day of September, 1970, at ..... o'clock ..... m., (signed)  
*[Signature]* CO. SURVEYOR by .....  
(COUNTY OFFICIAL) (DEPUTY)