


CERTIFIED RECORD OF LAND CORNER MONUMENTS

**History of original corner establishment:**

Corner was set originally by Caudle in 1880. He set a 10"x8"x8" stone and built a stone mound. In 1899 County Surveyor set a post and scribed 2 Alder B.T.S. Markham has tied to this corner but there is no record as to who set the axle



**Description of corner evidence found:**

a 1½" axle driven beside a 12" x 10" x8" stone in a stone mound. Forest Service location poster on fence post. Monument approx 30 feet east of Wolf Creek at the end of an old fence running east. Caudle makes a creek call 1.5 chains west of corner but ground is flat and creek could have changed course.

**Description of monument and accessories established to perpetuate the original location of this corner**

a 2" x 30" pipe with brass cap marked

T3S	R9W
21	22
28	27
1970	
920	

- Reset Axle beside pipe and reset stones
- A 50" maple brs. N 16E 92 ft.
- Bark scribed S22BT
- A 20" Spruce brs. S8E 89<sup>0</sup> ft.
- Scribed S27BT
- A 35" Spruce brs. S. 61W 105<sup>8</sup> ft.
- Scribed S28BT
- A 18" Alder brs. N. 59W 73<sup>2</sup> ft.
- Bark scribed T 3S R9W S21BT
- Set steel fence post 3 ft. South of pipe with Attn. Sign facing east.
- Placed B. T. tags on all B. T.'s

Office of County Surveyor County of TILLAMOOK  
 State of OREGON, I hereby certify that the within instrument was filed in this office  
 for record on the 9 day of SEPTEMBER, 1970, at        o'clock        m., (signed)  
John Paul CO. SURVEYOR by         
 (COUNTY OFFICIAL)



*Richard L Bryant*

