


CERTIFIED RECORD OF LAND CORNER MONUMENTS

History of original corner establishment:

Corner was originally set by Sam Caudle in 1880. He set a post and scribed 2 BTs. Lew Amort using a line call and an old scribed 3x3x24" stake restored corner with a brass cap and scribed an alder and spruce BT. A road was built near the corner destroying Amort's spruce BT and partially covered the alder and the brass cap.



Description of corner evidence found:

Found 2" pipe with 3" brass cap marked $\frac{1}{4}$
(Cap had been buried by road fill) S 20 | 21 (Amort, 1961)

from which

A 20" alder brs. N18E 19.4 ft
bark scribing partially covered by road fill

A 4x4" white post brs. S45W 1 foot

Description of monument and accessories established to perpetuate the original location of this corner

None

An 18" alder brs. N38W 9.3 ft - bark scribed $\frac{1}{4}$ S20 BT 920

Attached an attention sign to the white post
Painted red band and placed BT tags on BTs.

Office of COUNTY SURVEYOR of County of TILLAMOOK
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 9th day of SEPTEMBER, 1970, at o'clock m., (signed)
[Signature] COUNTY SURVEYOR by

REGISTERED
OREGON
LAND SURVEYOR

[Signature]
JULY 17, 1970
RICHARD L. BRYANT
920