


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1882 by General Land Office Contract Survey.

Original survey record states: Set post 4ft Long 6" in diameter, 12" in ground marked 1/4 S on West Face. from which Elder 8" in diameter bears N84°E 20 1/2 Ks, marked 1/4 S BT, Elder 7" in diameter bears S16°E 8 1/2 Ks marked 1/4 S BT.



Description of corner evidence found:


Found no evidence of original 1/4 corner

SEE MAP B-985  
FOR REVISED CORNER  
POSITION 7-17-81  
Allan Duncan C.S.

Description of monument and accessories established to perpetuate the original location of this corner

Set by proportional measurement a 2" x 30" galvanized iron pipe flared at the bottom and a brass cap riveted on top extending 3" above the ground.

Stamped Disk



Set steel post with forest service sign 2.0ft North of monument.

New Bearing Trees as follows:

11" Fir scribed " 1/4 S3 BT " S62°40'W 6.20ft.

17" Spruce scribed " 1/4 S2 BT " S81°E 22.95 ft.

Placed USFS Bearing tree signs on each tree Breast high & facing monument.

Office of COUNTY SURV County of TILLAMOOK  
State of OREGON, I hereby certify that the within instrument was filed in this office  
for record on the 16 day of JUNE, 1971, at 9 o'clock A.m., (signed)  
Allan Duncan C.S. by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED  
OREGON  
LAND SURVEYOR

August C. Giering  
JULY 12, 1963  
AUGUST C. GIERING  
608

CLARK & GROFF ENGINEERS, INC.  
3276 COMMERCIAL STREET S. E.  
SALEM, OREGON

BOOK 5