


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: *None.*



Description of corner evidence found: *None.*

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2" x 30' galvanized iron pipe, flared at the bottom and a brass cap riveted on top and extending 4" above ground.

Stamped disk →



Set steel post with Forest Service Sign 5.0 ft South of Monument.

New bearing trees as follows:

11" Spruce scribed " W/6 534 BT " N4°12'E 44.10 feet.

40" Spruce scribed " W/6 53 BT " S31°30'E 65.66 feet.

Placed U.S.F.S. sign on each bearing tree breast high facing monument.

Office of County Surveyor County of OR Tillamook
 State of OREGON, I hereby certify that the within instrument was filed in this office
 for record on the 10th day of JUNE, 1971, at 9 o'clock A.m., (signed)
John C. Giering by _____
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
 OREGON
 LAND SURVEYOR

BOOK 5

CLARK & GROFF ENGINEERS, INC.
 3276 COMMERCIAL STREET S. E.
 SALEM, OREGON

August C. Giering
 JULY 12, 1963
 AUGUST C. GIERING
 608