


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: *NONE*

IN T55 R10W W.M.




Description of corner evidence found: *NONE*

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2" x 30" galvanized iron pipe, flared at the bottom and a brass cap riveted on top and extending 3" above the ground

Set steel posts with Forest Service signs 5.0ft west of monument.

Stamped Disk →



New Bearing trees as follows:

10" Cedar scribed "N 1/16 54 BT" N 66° 38' W 16.98 ft.

19" Fir scribed "N 1/16 53 BT" N 9° 02' E 62.97 ft

Placed U.S.F.S. Bearing tree signs on each tree breast high facing monument.

Office of COUNTY SURVEYOR County of TILLAMOOK

State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 16 day of JUNE, 1971, at 9 o'clock A.m., (signed)

[Signature]

(COUNTY OFFICIAL)

by

(DEPUTY)

CLARK & GROFF ENGINEERS, INC.
3278 COMMERCIAL STREET S. E.
SALEM, OREGON

REGISTERED
OREGON
LAND SURVEYOR

[Signature]
JULY 12, 1963
AUGUST C. GIERING
608

BOOK 5

Form R6-7100-57 (9/66)

BOOK 5