


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: *NONE.*




Description of corner evidence found: *NONE*

Description of monument and accessories established to perpetuate the original location of this corner

Set 2" x 30" galvanized iron pipe, flared at the bottom and a brass cap riveted on top, extending 6" above the ground.

Set steel posts with Forest Service signs 5.0ft North and 5.0ft West of monument.

Stamped Disk →



New bearing trees as follows:

11" Fir scribed "E 1/4 S 10 BT" S 17° 46' W 21.12 ft.

9" Fir scribed "E 1/4 S 3 BT" N 15° 31' W 21.88 ft.

Placed USFS bearing tree sign on each tree breast high facing monument.

Office of County Surveyor County of Tillamook
 State of OREGON, I hereby certify that the within instrument was filed in this office
 for record on the 16 day of JUNE, 1971, at 9 o'clock A.m., (signed)
[Signature] (COUNTY OFFICIAL) by _____ (DEPUTY)

REGISTERED
 OREGON
 LAND SURVEYOR

CLARK & GROFF ENGINEERS, INC.
 3276 COMMERCIAL STREET S. E.
 SALEM, OREGON

[Signature]
 JULY 12, 1963
 AUGUST C. GIERING
 608

BOOK 5

Form R6-7100-57 (9/66)

BOOK	5
------	---