


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

From Original Notes:

- 40.00 Set a fir post 5 feet long, 4 inches diameter for 1/4 corner; from which:
 - A fir, 40 inches diam., brs. N.22° E. 30 lks.
 - A fir, 36 inches diam., brs. S.4° E. 248 lks.
- 44.50 Brook, 5 links wide, runs South.



Description of corner evidence found:

Found remnants of original BT's. Both are now rotten snags with no scribing visible. The post is no longer apparent, but the corner checks with the call distance to the brook 4.5 chains to the East. The bearing trees are now:

- 44 inch Snag N. 22° E. 19.8 feet;
- 65 inch Snag S. 4° E. 163.7 feet.

Description of monument and accessories established to perpetuate the original location of this corner

Set a 2" x 30" iron post with brass cap marked

1/4
S 35
S 2
1971
OLS 816

from which:

- a 35" fir bears N. 77½° W. 18.4 feet, scribed BT 1/4 S 35;
- a 15" alder bears S. 32° E. 25.0 feet, scribed BT 1/4 S 2;
- a 23" fir bears N. 79½° E. 39.1 feet, scribed BT 1/4 S 35.

All bearing trees are tagged and have a red band painted on them.
Set a steel fence post 6 feet East of corner.

Witnesses present: Kenneth Wightman
William Parks

Office of County SHERMAN County of TILLAMOOK
 State of OREGON, I hereby certify that the within instrument was filed in this office
 for record on the 8th day of SEPTEMBER, 1971, at 9 o'clock A.m., (signed)
[Signature] by [Signature]
 (COUNTY OFFICIAL) (DEPUTY)