


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally established by John Meldrum in 1872. At that time he set a post and scribed a 6" Spruce N.68°E. 8 links and 36" Spruce S.85°W. 116 links.

(Contract Survey)



Description of corner evidence found:

In 1890 the G.L.O. ran North through T.6S., R.10W. and set closing corners for the N.E. and N.W. corners of Section 6. This would make this ½ corner common to Section 31 only. In 1898 the County Surveyor found the corner and the 36" Spruce had blown down. In 1947, Wilbur Markham set a 7/8" iron pipe "½ Corner on the TWP line N.89°-19' W. 2865ft." from which a 60" Spruce growing as a twin with a 50" Spruce bears N.35°W., 192 feet.

I could find no evidence of the original corner on its accessories. I did find Markham's BT but no pipe.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2"x36" Iron pipe with a flared bottom and a brasscap riveted to the top marked:

T.5S., R.9W.
SC
½ S 31
1971
O.L.S. 816

Based on single proportionate measurement.

I scribed the following BT's and placed tags and painted a white band on them.

- 48" Spruce N.28°E. 746 ft., mkd. "½ S31SC BT"
- 41" Spruce N.68°E. 457 ft., mkd. "½ S31SC BT"

The point established from Markham's twin BT bears S.82°-56'-45"E. 224.36 feet.

I erected a small stone mound around the brasscap and set a 6 foot steel post with an "Attention" sign 3 feet West

Office of COUNTY SURVEYOR, County of TILLAMOOK
State of OREGON, I hereby certify that the within instrument was filed in this office
on record on the 12th day of October, 1971, at 8:40 o'clock A.M., (signed)
J. L. Conlin (COUNTY OFFICIAL) by *Kenneth M. Wightman* (DEPUTY)

Witnessed:

M. Yinger Set this 23rd day of September 1971

BOOK 5

REGISTERED
OREGON
LAND SURVEYOR

Kenneth M. Wightman
JULY 17, 1970
KENNETH M. WIGHTMAN II
197