

CERTIFIED RECORD OF LAND CORNER MONUMENT

History of original corner establishment:

None

DIAGRAM
T.5S., R.9W.
N 1/16
S28/S27

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2"x36" Iron pipe with a flared bottom and a brasscap riveted to the top marked:

T.5S., R.9W.
N 1/16
S28/S27
O.L.S. 816

I scribed the following BT's and placed tags and painted red bands on them;

14" Alder N.75°W. 14¹/₂ ft., mkd. "N 1/16 S28BT"
45" Spruce N.16°E. 46¹/₂ ft., mkd. "N 1/16 S27BT"

I erected a small stone mound around the brasscap and set 6 foot steel posts with "Attention" and "Property Boundary" signs 4¹/₂ feet East and 3 feet South.

Set this 20th day of September 1971

Witnessed:

M. Yinger

REGISTERED
OREGON
LAND SURVEYOR

Kenneth M. Wightman
JULY 17, 1970
KENNETH M. WIGHTMAN II
942

Office of COUNTY SURVEYOR County of TILLAMOOK
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 12th day of SEPTEMBER, 1971, at 8:30 o'clock A.m., (signed)
[Signature] by COUNTY SURVEYOR
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/66)