


REGISTERED PROFESSIONAL LAND SURVEYOR  
KENNETH M. WIGHTMAN II  
942

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was established by the GLO in 1879. They set a post and marked:

"A 20" <sup>fir</sup> ~~Snag~~, N. 34° E., 56 links  
"A 30" <sup>fir</sup> ~~Snag~~, S. 47° W., 76 links



Description of corner evidence found:

I found a 3/4" pipe 20" above ground tied to an old post (no markings visible). Both witnesses are in place but distance calls seem to be to the faces rather than the center of the tree. The original scribing is still visible on the N.E. BT. I also found two BT's marked by M. Whitmore in 1962.

"16" Alder N. 59° W. 26ft., Bark scribed "½ S.32 BT"  
10" Fir N. 52½° E. 93ft., "

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2" x 30" Iron pipe with a flared bottom and a brasscap rivited to the top marked:

T.4S. R.9W.  
¼  
S.32 / S.33  
1971  
O.L.S. 816

I tied to the existing BT's and placed new tags and painted red bands on them.

30" Snag N.34°E. 38<sup>4</sup>ft. (37<sup>0</sup> ft. to face)  
40" Snag S.47°W. 51<sup>9</sup>ft. (50<sup>2</sup> ft. to face)  
16" Alder N.59°W. 26<sup>0</sup> ft., mkd "½ S.32BT"  
11" Fir N.48°E. 90<sup>1</sup> ft., (scar visible)

I erected a stone mound around the brasscap and reset the old post and pipe 2 feet South. I also set a 6' steel post with an "Attention" sign 3 feet North.

Witness: Set this 27th day of September 1971

M. Yinger  
Office of COUNTY SURVEYOR County of TILLAMOOK  
State of OREGON, I hereby certify that the within instrument was filed in this office  
for record on the 8<sup>th</sup> day of MARCH, 1972, at 5 o'clock P. m., (signed)  
John L. Conlin by Co. Surveyor  
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED PROFESSIONAL LAND SURVEYOR

Kenneth M. Wightman

OREGON  
JULY 17, 1870  
KENNETH M. WIGHTMAN II  
942