

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

This corner was originally established in 1890, under contract No. 555, 81.12 chs. North of $\frac{2}{11} \frac{1}{12}$. A post was set, from which:

- 30" Hemlock S 89 1/2° W 396 lks.
mkd "T 6 S R 11 W S 1 CC BT"
- 24" Alder S 50° E 414 lks.
mkd "T 6 S R 11 W S 6 CC BT"
- 18" X 18" X 12" pit 10 lks. North with a raised mound alongside.

In 1947 W. Markham, LS No. 1842, found the Hemlock BT and set a pipe from which a:

- 30" Spruce S 25° E 175.9 ft.
- 30" Spruce S 63 1/2° W 201.9 ft.



Reference:

Plat dated July 1973 by
Timberland Services, Inc.
under my stamp.

Description of corner evidence found:

I found a 3/4" pipe and the SE Spruce BT.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and a brasscap riveted to the top marked:

T 5 S R 11 W
S 36
S 1 S 6
R 11 W R 10 W
T 6 S
CC
1973
RLS 942

From which a:

- 22" Alder S 87° W 181.9 ft.
mkd "T 6 S R 11 W S 1 CC BT"
- 38" Spruce S 25° E 176.7 ft.
scar visible

Witnessed: M. Jackson

Office of County Surveyor County of TILLAMOOK
State of OREGON I hereby certify that the within instrument was filed in this office
for record on the 20th day of AUGUST, 1973, at 9:40 o'clock A m., (signed)
[Signature] by _____
(COUNTY OFFICIAL) (DEPUTY)

Set this 25th day of July 1973.

BOOK 5 Edgar R Cook 230

Graduate Forest Engineer
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.
P.O. Box 668 - Albany, Ore. 97321
Phone: 928-3539

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kenneth M. Wightman

OREGON
JULY 17, 1970
KENNETH M. WIGHTMAN II
942