

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner had never been established.

DIAGRAM S
C-S-NW 1/64
Section 6

Reference:

Plat dated July 1973 by
Timberland Services, Inc.
under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and a brasscap riveted to the top marked:

T 6 S R 10 W
S 6

C-S-NW
1/64

1973
RLS 942

By proportional measurement.
From which a:

- 50" Spruce S 32° E 30.0 ft.
mkd "CSNW 1/64 S 6 BT"
- 12" Hemlock S 1° 3 15.0 ft.
mkd "CSNW 1/64 S 6 BT"

Witnessed: M. Jackson

Office of COUNTY SURVEYOR, County of TILLAMOOK
State of OREGON I hereby certify that the within instrument was filed in this office
for record on the 20th day of AUGUST, 1973, at 8⁴⁷ o'clock a.m., (signed)

John Condit
(COUNTY OFFICIAL) by _____ (DEPUTY)

Set this 25th day of July 1973.

BOOK 5 ' *Edgar R Cook*

247

Graduate Forest Engineer
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.
P.O. Box 668 - Albany, Ore. 97321
Phone: 928-3539

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kenneth M. Wightman

OREGON
JULY 17, 1970
KENNETH M. WIGHTMAN II
942