

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner had never been established.

DIAGRAM T
Section 6
SE-NW 1/64

Reference:

Plat dated July 1973 by
Timberland Services, Inc.
under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and a brasscap riveted to the top marked:

T 6 S R 10 W

S 6

SE-NW

1/64

1973

RLS 942

by proportional measurement.

From which a:

46" Hemlock S 22° E 31.5 ft.

mkd "S 22° E 31.5 ft. BT"

34" Hemlock N 25° E 22.2 ft.

mkd "N 25° E 22.2 ft. BT"

Witnessed: M. Jackson

Office of COUNTY SURVEYOR County of TILLAMOOK
State of OREGON I hereby certify that the within instrument was filed in this office
for record on the 26th day of August 1973, at 8⁴⁵ o'clock A.M., (signed)

John Carter
(COUNTY OFFICIAL) by _____ (DEPUTY)

Set this 26th day of July 1973.

BOOK 5

Edgar L Cook

248

Graduate Forest Engineer
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.
P.O. Box 668 - Albany, Ore. 97321
Phone: 928-3539

