

County Surveyor's Record, Tillamook County, Oregon

Feet

T3S R9W

36

1 N 1/4

T4S R9W

1974 650

from which

- A 24" Fir bears S33°E, 14.2 feet to face
Scribed N 1/4 S 1 BT.
- A 12" Fir bears S28°W, 23.8 feet to face
Scribed N 1/4 S 1 BT 650.

A 2" iron pipe of unknown origin bears East 6 feet. I removed.

2621.40 The position for the original 1/4 corner to Section 36 as established by Henry Meldrum. This is now an angle point on the true Township Line, which is a square wood post. I replaced this with a 2 1/2" x 30" iron post with brass cap marked

MELDRUM

T3S R9W

36
----- 4 PT
1
T4S R9W

1974 650

from which

- An old Fir stub bears N21°E, 32 lks to face
No scribing visible but there is an old face.
- An old Fir stub bears S61°E, 44 lks to center
This is an original BT--no scribing visible.
- A 29" Fir bears N20°W, 1.2 feet to face
Face healed.
- A 22" Fir bears S57°E, 15.2 feet to face
Scribed 1/4S 1 BT--Bark scribed 650 above face.

The true S 1/4 corner to Section 36 as established by Caudle bears S23°35'58"W, 172.45 feet. At this point, I found a 1/2" iron pipe alongside the original stone with 1/4 still visible. I replaced with a 2 1/2" x 30" iron post with brass cap marked

IN T4S R9W

CAUDLE

. AM

S 36 1/4

1974 650

from which

- A 48" Fir bears N64°E, 36.5 feet slope distance to face
Scribing just visible.
- A 54" Fir bears S64°E, 18.5 feet to face
Scribed 1/4 BT--Bark scribed 650 above face.

See map B-661