


# County Surveyor's Record, Tillamook County, Oregon

Feet

A 16" Hemlock bears S77°E, 38.2 feet to face  
Scribed S1 BT 650.

5268.97 The original corner to Sections 35, 36, 1, and 2 as established by Henry Meldrum, now an angle point on the Township Line, which is a 1/2" iron pipe with a white painted cedar post alongside. I replaced this monument with a 2 1/2" x 30" iron post with brass cap marked




from which

- An old Fir stub bears N44°W, 78 lks  
Old axe marks visible, but not original.
- An old Fir stub bears N56°E (168 lks)  
An original BT.
- An old Fir stub bears S51°E (S45E), 214 lks  
This is an original BT.
- A 40" Fir (Red Fir) bears S51 1/2°E, 23.8 feet  
This is Douglass' BT--face partially healed--  
scribing is not visible.
- A 36" Fir bears N28°E, 29.1 feet  
No face showing--probably Sappington's BT.
- A 14" Alder bears S28°W, 23.1 feet  
This could also be Sappington's BT--portion of the  
tree is broken.
- A 50" Fir bears N38°E, 23.8 feet to a nail in face  
Scribed S36 BT with 650 bark scribed.

The true corner to Sections 35 and 36 bears S25°38'51"W, 117.02 feet.  
This is an iron post with brass cap as remonumented by me in 1969.  
The notes to this are on file in the Tillamook County Surveyor's office.

Restamped the brass cap as follows:



Continuing on the true line between T3 and 4S, R9W  
N89°31'40"E

- 1200 Branch, 12 feet wide, course N20°W
- 1600 Rocked road
- 2579.67 The point for the N 1/4 corner to Section 1. I set a 2 1/2" x 30" iron post with brass cap marked

*See map B-661*