

County Surveyor's Record, Tillamook County, Oregon

7

Feet from which

- A Fir snag bears N31 $\frac{1}{2}$ °E, 34.0 feet
This is an original BT--old axe marks still visible.
- A Fir stub bears S49°E, 35.6 feet
Old BT--scribing still visible.
- A 20" Alder bears N70°W, 33.0 feet
Bark scribed--1/4 S31 BT.
- A 40" Fir bears N66 $\frac{3}{4}$ °E, 62.0 feet
Face healed over.


Continuing on line between T3 and 4S, R9W

S89°36'44"E

- 3498 Descend
- 4080 Branch, 4 feet wide, course N10°E
- 4346 Spur bears north-south
- 4574 Branch, 3 feet wide, course N60°W
- 4939.15 Closing corner to Sections 5 and 6, bears South 9.84 feet.

Found a maple post for the corner point scribed CC S6 on the north face and CC S5 on the west face. I replaced this post with a 2 $\frac{1}{2}$ " x 30" iron post with brass cap marked

T3S R9W



from which

- An 18" Alder bears S22 $\frac{1}{2}$ °W, 78.2 feet
This is Branson's BT. There is a face but no scribing is visible.
- An old Fir snag bears S60°E, 64.4 feet
Branson's BT--no scribing visible.
- A 20" Fir bears S42°E, 47.6 feet to face
Face healed--scribing not visible.
- A 36" Fir bears S22°W, 22.5 feet to face
Face healed--scribing not visible.
- A 30" Fir bears S54°W, 43.5 feet to face
Face healed--scribing not visible.

Laid maple post alongside new monument.

Continuing on line

- 5339 Spur bears north-south
- 5412.49 The corner to Sections 31 and 32.

Found a Fir post with S31 scribed on the west side and S32 on the east for corner. I replaced this post with a 2 $\frac{1}{2}$ " x 30" iron post with brass cap marked

See map B-661