


17

FIELD NOTES FOR SETTING THE
CE 1/6 COR. SEC. 18, T3N, R9W, W.M.
(SEE MY SURVEY OF SEC. 18 & 19
FOR POSITION OF THIS CORNER)

I SET FLUSH A 1 1/2" X 36"
CONCRETE FILLED, GALV. I.P.
WITH 2" BRASS CAP STAMPED
AS SHOWN:



FROM WHICH I SCRIBED
TWO BEARING TREES

A 18" HEMLOCK BEARS
S 20° W 41.50' TO FACE
SCRIBED "CE 1/6 S 18 BT"

A 34" HEMLOCK BEARS N 28° W
27.50' TO FACE SCRIBED
"CE 1/6 S 18 BT"


WITNESSES: K. FOESTE, L.S. 849
DATE: 12/74 *William Thompson*

Allen Hoffmann

18

FIELD NOTES FOR SETTING THE
NE 1/6 COR., S 18, T3N, R9W, W.M.
(SEE MY SURVEY OF SEC. 18 & 19
FOR POSITION OF THIS CORNER)

I SET FLUSH A 1 1/2" X 36"
CONCRETE FILLED, GALV. I.P.
WITH 2" BRASS CAP STAMPED
AS SHOWN:



FROM WHICH I SCRIBED
TWO BEARING TREES:

A 15" FIR BEARS S 14° W
6.95' TO FACE SCRIBED
"NE 1/6 S 18 BT"

A 18" FIR BEARS S 53° E 19.90' TO
FACE SCRIBED "NE 1/6 S 18 BT"

WITNESSES: K. FOESTE, L.S. 849
DATE: 12/74 *William Thompson*

Allen Hoffmann

REGISTERED
PROFESSIONAL
LAID SURVEYOR

OREGON
JULY 12, 1968
MARL F. FOESTE
0849