


FIELD NOTES FOR RE-ESTABLISHING THE  
 LOST CORNER TO SEC. 18 & 19, T3N,  
 R9W, AND SEC. 13 & 24, T3N, R10W,  
 W.M. DATE: NOV. 1975

ALL EVIDENCE OF THE ORIGINAL  
 POSITION OF THIS CORNER HAS BEEN  
 LOST. AT THE SINGLE PROPORTIONED  
 DISTANCES OF N0°-25'-27"W 5,267.32  
 FT. FROM THE S.W. CORN. SEC 19 &  
 S0°-25'-27"E 2,633.66 FT. FROM  
 THE W ¼ CORN. SEC. 18 I SET A  
 1½" X 36" CONCRETE FILLED, GALVANIZED  
 IRON PIPE WITH A 2" BRASS  
 CAP STAMPED AS SHOWN:



I SET FOUR BEARING TREES  
 THAT BEAR AS FOLLOWS  
 FROM THIS MONUMENT:

- 5" HEMLOCK BEARS N31°E
- 13 65" FT. TO FACE SCRIBED "BT"
- 6" HEMLOCK BEARS N10°W
- 13 25" FT. TO FACE SCRIBED "BT"
- 10" HEMLOCK BEARS "S24 BT" S65W
- 21 45" FT. TO FACE SCRIBED "S24 BT"
- 32" HEMLOCK BEARS S20°E
- 20 0" FT. TO FACE SCRIBED "T3NR9WS19BT"

WITNESSES:

*Oliver Hoffmann*  
*Oliver Hoffmann*

DATE: 11/74

see Book 4  
 p. 26 & 78  
 QICMS

