

County Surveyor's Record, Tillamook County, Oregon

CHAINS

REWITNESSED CORNER FOR STATE OF OREGON--DEPARTMENT OF FORESTRY

Section corner common to Sections 1, 2, 35 and 36, T2&3N, R7W, W.M., Tillamook County, Oregon.

ORIGINAL

Stone 24" x 18" x 5" (missing, OSBF iron pipe below, in place) from which a:

- 24" Hemlock bears N78°E 20 lks.; missing.
- 20" Fir bears S3°E 51 lks.; now a 24" stump with scribe 2 visible.
- 24" Hemlock bears S24°W 50 lks.; now a 26" stump, no scribes visible.
- 20" Fir bears N13°W 50 lks.; missing.

RESTORATION by L. W. Amort, July 14, 1955.

1½" x 36" galvanized iron pipe with 3" bronze cap 33" in ground (in place) from which a:

- 52" Fir stump bears N87°E 76.4 ft.; missing, destroyed by slide.
- 30" Fir stump bears N57°E 143.8 ft.; missing, destroyed by slide.
- 10' high by 12' wide rock face bears S64½°W 28.0 ft.; marks BO on upper left corner, in place.

REWITNESSED

Var. 21½°E

From above corner monument in mound of rock a:

- 11" Fir bears N52½°E 6.1 ft. to face; scribed T3N R7W S36 BT RS 707.
- 9" Fir bears N64°W 24.9 ft. to face; scribed T3N R7W S35 BT.
- 7" Fir bears S78°E 13.6 ft. to face; scribed T2N R7W S1 BT.
- 5" Fir bears S23°W 24.0 ft. to face; scribed T2N R7W S2 BT.

Set 4" x 4" x 72" white painted Cedar post 1.5 ft. SE of corner pipe. Oregon State Forestry Department metal location poster on 11" Fir BT.

Dated December 16, 1974

Rewitnessed by Steve Ellis under my direction.  
Steve Ellis, Compassman

Present and witnessed by Terry Withrow

