

County Surveyor's Record, Tillamook County, Oregon

CHAINS

RESTORED CORNER FOR STATE OF OREGON--DEPARTMENT OF FORESTRY

One quarter corner common to Sections 2 and 3, T2N, R7W, W.M., Tillamook County, Oregon.

ORIGINAL

Basalt stone 16" x 15" x 10" (found stone out of place, about 4' East, downhill) from which a:

60" Larch bears N16°E 56 lks.; now a 60" shell of a stump, axe work visible where bottom of face was.

50" Fir bears S7°W 54 lks.; now a 50" stump with scribes 1/4 S visible.

Note: Using slope disances both original BTs fit for distance and bearing.

RESTORED

Var. 21½°E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S2 S3 1974 RS 707," 35 inches in ground, with original stone on the West side of corner pipe, from which a:

8" fir bears S77°W 23.7 ft. to face; scribed 1/4 S3 BT RS 707.

9" Hemlock bears N16°E 17.2 ft. to face; scribed 1/4 S2 BT.

Set 4" x 4" x 60" white painted Cedar post 1.0 ft. NE of corner pipe. Oregon State Forestry Department metal location poster on 3" Fir S23°E 0.6 feet.

Dated December 16, 1974

Restored by Loren R. Steele under my direction.  
Loren Steele, Forest Engineer

Present and witnessed by Terry Withrow

