


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Survey of Fenton and Maloney 1887  
Set a post 4' long 4" square in ground marked  
1/4 S on W from which  
a fir, 30" diam., bears N 62° E, 10 lks. dist.  
marked 1/4 S BT  
a fir, 24" diam., bears N 49° W, 26 lks. dist.  
marked 1/4 S BT




Description of corner evidence found:

Found 2"x2"x36" wooden post set by L. Whitmore in 1963 from original BTs  
Found 36" fir stump N 62° E 6.6' to face of blaze with portion of original scribe  
showing with BT sign facing cor.  
Found 34" fir stump N 49° W 17.2' with portion of original blaze  
Found 10" fir bearing S 52° E 36.3' to side center blaze healed over with BT sign  
facing cor.  
Corner is in stand of young fir 60' S old logging road running N 60° E

Description of monument and accessories established to perpetuate the  
original location of this corner

Set 3" brass cap and 2" iron pipe 6" above ground, stamped:  
Set steel fence post with Do Not Destroy sign 3 feet N  
of monument  
Placed BT sign on 34" fir stump and painted face of blaze  
Painted face of blaze on 36" fir stump  
A fir 11" in diameter bears N 5° E 12.5 feet to side center  
scribed "1/4 S6" on upper blaze with BT and brass washer on  
lower blaze with Bearing Tree sign facing corner and  
Attention sign on back - painted 6" red band and face of blaze



*See Map B-701*



Office of COUNTY SURVEYOR County of TILLAMOOK  
State of OREGON, I hereby certify that the within instrument was filed in this office  
for record on the 17<sup>th</sup> day of NOVEMBER  
J. L. Carlin, C.S. by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)