

TILLAMOOK COUNTY

REMONUMENTATION OF CORNER  
by James B. Iremonger, Jr.

This corner is located in a active timber sale contract area. The new bearing trees will be soon cut, but will be treated and preserved after cutting by removing all bark, flooding the stumps with preservative and covering the top of each with galvanized metal.

$\frac{1}{4}$  corner between Sections 23/24, T.3S., R.7W., W.M.

Magnetic Declination used  $21\frac{1}{2}^{\circ}$ E

Original Notes 1873 by Henry Meldrum  
called for:

Stone 12x9x8 for  $\frac{1}{4}$  sec. cor.

FOUND:

Original stone 12"x9"x8" firmly set in the ground with  $\frac{1}{4}$  marked on the west face.  
Steel fence post alongside.

NEW:

Set a  $\frac{3}{4}$ " x 36" galvanized iron pipe 30" in the ground on the north side of the stone monument.

SCRIBED:

Fir, 26", S68 $^{\circ}$ E, 18.8 FT. ( $\frac{1}{4}$ S24BT)  
Fir, 13", N58 $^{\circ}$ W, 11.2 FT. ( $\frac{1}{4}$ S23BT)

Witnessed:

5-4-76

John C. Hanks, BLM

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*James B. Iremonger, Jr.*

OREGON  
JULY 14, 1967  
JAMES B. IREMONGER, JR.  
800



IN REPLY REFER TO

# United States Department of the Interior

BUREAU OF LAND MANAGEMENT  
District Office  
3550 Liberty Road S.  
P. O. Box 3227  
Salem, Oregon 97302

MAY 10 1976

Mr. John L. Carlich  
Tillamook County Surveyor  
County Court House  
Tillamook, Oregon 97141

Dear Mr. Carlich:

Enclosed are the notes for remonumentation and new bearing trees  
at the  $\frac{1}{4}$  corner between sections 23/24, T.3S., R.7W., W.M.

Sincerely Yours,

James B. Iremonger, Jr.  
Forest Management Specialist

Enclosure

BOOK 5



372