

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**


History of original corner establishment:

Corner established by W. P. Wright in 1882 under G. L. O. Contract No. 442. For this corner Wright set a scribed post, from which he scribed two bearing trees: A Spruce 14 ins. bears N 88° E 58 lks dist. A Spruce 12 ins. diam. bears S 10° W 57 lks. dist.

On County Survey Plat A-165 G.E. Davis, Deputy County Surveyor, Shows the following bearing trees at this corner: Spruce 12" diam S 10° W 37.5 ft. Spruce 14" diam N 88° E 38.0 ft. Davis does not say whether he set these trees or found them. No date is given on Davis' survey.


In county Survey Book P-16, Page 47, C. A. Dunn reports the following bearing trees at this corner: 40" Spruce S 52° 29' W 31.0 ft. 30" Spruce N 52° 50' E 25.5 ft. Dunn does not say whether he found or set these B. T's.

In County Survey Book 3, Page 301, C. G. Collard, L.S. 376, reports: " on May 8, 1969, I found the two Spruce BTs ( now rotting stumps) with a scribed 'BT' plainly evident on both. From these original bearing trees I set a 3/4" iron pipe with 3 inch brass cap for the 1/4 corner. I marked new bearing trees as follows: 16" Fir brs. N 39° E 41.8 ft. scribed BT-S25-376. 14" Fir brs. S 75° W 23.7 feet, scribed BT -S36-376.



Description of corner evidence found:

At the corner I found Collard's 3 inch brass cap monument on a 3/4" iron pipe that sticks 24 inches above ground. The monument is set in the bottom of a small creek that runs North and South. I also found both original B. T's: 20" rotten Spruce Stump brs. S 86° E 38.0 ft. to face with portion of original scribing visible. Case hardened core of rotten Spruce stump brs. S 13° W 37.0 ft. to face with full original scribing still visible. Collard's bearing trees are still present and they bear as reported by him in May, 1969. Collard's Brass cap is stamped as shown bellow: I did not find any trace of the bearing trees reported by G. E. Davis, or C. A. Dunn.



Description of monument and accessories I established to perpetuate the original location of this corner:

I, Karl F. Foeste, hereby certify that I found and witnessed the above corner as described herein in October, 1976.

*Survey B-1-3-1-1-1*

Witnesses: *Harold A. Engberg*  
*Allen F. Hofmann*

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Karl F. Foeste*

OREGON  
JULY 12, 1968  
KARL F. FOESTE  
0849

Recorded in the office of Surveyor, County of Tillamook

State of Oregon, I hereby certify that the within instrument was filed in this office

for record on the 15<sup>th</sup> day of December, 1976

*[Signature]*  
(county official)

by \_\_\_\_\_ (deputy)

**KARL F. FOESTE, Registered Professional Land Surveyor of the State of Oregon**