

Remonumentation of Certain Original Corner Points,  
T. 3 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S R 10 W

$\frac{1}{4}$  S 22  
S 27

1978

Reset iron pipe and set a 5 ft. steel fence post alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 15 and 16, perpetuated and recorded by Leonard Whitmore, Deputy County Surveyor, in 1975, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, from which an original bearing tree:

A hemlock, 35 ins. diam., bears N.  $40^\circ$  E., 37 lks. dist., with scribe marks BT visible on open blaze.

and a bearing tree mkd. by Whitmore

A hemlock, 15 ins. diam., bears N.  $67^\circ$  W., 29 lks. dist., with scribe marks  $\frac{1}{4}$  S16 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S R 10 W

$\frac{1}{4}$   
S 16 | S 15

1978

Reset iron pipe and set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by Mervin Whitmore, Deputy County Surveyor, in 1954, monumented with an iron pipe, 1 in. diam., firmly set, projecting 20 ins. above ground, from which the remains of the original bearing trees:

A decayed hemlock stump, size indeterminate, bears S.  $75^\circ$  W., 79 lks. dist., no marks visible on open blaze.

A root hole, bears N.  $59^\circ$  W., 34 lks. dist., with a down and decayed hemlock alongside, size indeterminate, with scribe marks BT visible on open blaze.

and bearing trees mkd. by Whitmore

A fir, 14 ins. diam., bears N.  $55^\circ$  E.,  $17\frac{1}{2}$  lks. dist., with healed blaze.

A fir, 14 ins. diam., bears S.  $15^\circ$  W., 37 lks. dist., with healed blaze.