

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

T 3 S R 10 W
S 22 | S 23
S 27 | S 26
1978

Reset wood post and set a 5 ft. steel fence post
alongside iron post.

The cor. of secs. 21, 22, 27, and 28, perpetuated and
recorded by Mervin Whitmore, Deputy County Surveyor,
in 1958, determined at record bearing and distance from
the remains of the original bearing trees:

A decayed cedar snag, size indeterminate, bears
N. 20° E., 66 lks. dist., with scribe mark
S visible on open blaze.

A decayed fir snag, size indeterminate, bears
N. 83° W., 108 lks. dist., no marks visible.

and bearing trees mkd. by Whitmore

A fir, 17 ins. diam., bears S. 80° W., 27 lks.
dist., with healed blaze.

A cedar, 24 ins. diam., bears N. 25° W., 62½ lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins.
in the ground, to solid rock, and in a mound of stone,
3 ft. base, to top, with brass cap mkd.

T 3 S R 10 W
S 21 | S 22
S 28 | S 27
1978

from which new bearing trees

A hemlock, 24 ins. diam., bears N. 20° E., 36½
lks. dist., mkd. T3S R10W S22 BT.

A fir, 23 ins. diam., bears S. 55° E., 117½ lks.
dist., mkd. T3S R10W S27 BT.

Set a 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 22 and 27, perpetuated and re-
corded by Mervin Whitmore, Deputy County Surveyor, in
1952, monumented with an iron pipe, 1 in. diam., firmly
set, projecting 14 ins. above ground, from which the
remains of the original bearing trees:

A decayed fir stump, size indeterminate, bears
S. 72° W., 10 lks. dist., with scribe marks
¼ S BT visible on open blaze.

and bearing trees mkd. by Whitmore

A fir, 35 ins. diam., bears N. 6½° W., 30 lks.
dist., with healed blaze.

A fir, 29 ins. diam., bears S. 7° E., 20 lks.
dist., with healed blaze.

BOOK 6

100