

Remonumentation of Certain Original Corner Points,
T. 3 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 38 ins. diam., bears S. $43\frac{1}{2}^{\circ}$ W.,
68 lks. dist., with healed blaze.

A sawed fir stump, 26 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ W.,
165 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 3 S R 10 W	
S 23	S 24
S 26	S 25
1978	

from which new bearing trees

A hemlock, 7 ins. diam., bears N. 87° E., 23 lks.
dist., mkd. T3S R10W S24 BT.

A hemlock, 8 ins. diam., bears S. 28° E., $42\frac{1}{2}$ lks.
dist., mkd. T3S R10W S25 BT.

A hemlock, 7 ins. diam., bears S. 70° W., 29 lks.
dist., mkd. T3S R10W S26 BT.

A hemlock, 8 ins. diam., bears N. 27° W., 28 lks.
dist., mkd. T3S R10W S23 BT.

Set a 5 ft. aluminum fence post alongside iron
post.

The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, perpetuated and
recorded by Leonard Whitmore, Deputy County Surveyor, in
1959, monumented with the remains of the original corner
tree, a sawed and decayed fir stump, 14 ins. diam., with
scribe marks $\frac{1}{4}$ S visible on W. face, from which bearing
trees mkd. by Whitmore:

A fir, 38 ins. diam., bears S. 34° E., 29 lks.
dist., with healed blaze.

A fir, 30 ins. diam., bears S. 68° W., $29\frac{1}{2}$ lks.
dist., with healed blaze.

At the corner point

In the center of the stump, set an iron post, 28 ins.
long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass
cap mkd.

T 3 S R 10 W	
S 23	S 24
1978	

Set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 26, 27, 34, and 35, perpetuated and
recorded by Leonard Whitmore, Deputy County Surveyor, in
1963, determined at record bearing and distance from the
remains of the original bearing trees: