

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which a new bearing tree

A fir, 14 ins. diam., bears S. 59° E., 257½ lks.
dist., mkd. ¼ S21 BT.

No other suitable trees available within limits.

Deposit corner stone and set a 5 ft. steel fence
post alongside iron post.

(Remonumenting corners established by Henry Meldrum,
U. S. Deputy Surveyor, in 1879)

The ¼ sec. cor. of secs. 29 and 30, perpetuated and re-
corded by Mervin Whitmore, Deputy County Surveyor, in
1952, monumented with an iron pipe, 1 in. diam., firmly
set, projecting 10 ins. above ground, from which the
remains of the original bearing trees:

A decayed fir snag, size indeterminate, bears
N. 33° E., 41 lks. dist., with scribe marks
¼ visible on open blaze.

A decayed fir snag, size indeterminate, bears
N. 67° W., 69 lks. dist., no marks visible.

and bearing trees mkd. by Whitmore

A fir, 22 ins. diam., bears N. 76° E., 15 lks.
dist., with healed blaze.

A fir, 28 ins. diam., bears S. 67° W., 6 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 4 S R 9 W

¼
S 30 | S 29
1978

Reset iron pipe and set a 5 ft. steel fence post
alongside iron post.

The cor. of secs. 19, 20, 29, and 30, determined at
record distance from the remains of the original bearing
trees:

A cedar snag, 30 ins. diam., bears N. 42° E., 46
lks. dist., with scribe marks T4S S20 BT
visible on open blaze. (Record, N. 33° E.)

An alder, 24 ins. diam., bears S. 24° E., 23 lks.
dist., with healed blaze. (Record, S. 17° E.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.