

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir, 18 ins. diam., bears S. 33° W., 83½ lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 9 W
¼
S 22 | S 23
1978

Reset fir post and set a 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 14 and 15, perpetuated and recorded by Leonard Whitmore, Deputy County Surveyor, in 1960, monumented with the decayed remains of the original fir post, no marks visible, firmly set, projecting 14 ins. above ground, from which the remains of the original bearing trees

A decayed fir snag, size indeterminate, bears N. 71½° E., 37 lks. dist., with scribe marks ¼ S14 BT visible on open blaze.

A decayed fir snag, size indeterminate, bears S. 86° W., 88 lks. dist., with scribe marks ¼ S15 BT visible on open blaze.

and bearing trees mkd. by Whitmore

A fir, 20 ins. diam., bears S. 49° E., 34 lks. dist., with healed blaze.

A fir, 46 ins. diam., bears S. 60° W., 54 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 9 W
¼
S 15 | S 14
1978

Reset fir post and set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 10, 11, 14, and 15, determined from the remains of the original bearing trees:

An alder, 14 ins. diam., bears N. 59¼° E., 43 lks. dist., with scribe marks S11 BT visible on open blaze.

An alder snag, 12 ins. diam., bears S. 51° E., 55 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, S. 58¼° E.)

An alder, 18 ins. diam., bears S. 61¼° W., 45 lks. dist., with healed blaze.