

Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which a new bearing tree

An alder, 20 ins. diam., bears N. 32° W., 69 lks. dist., mkd. T4S R9W S2 BT on bark.

No other suitable trees available within limits.

Reset iron pipe and set a 5 ft. aluminum fence post alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 12, perpetuated and recorded by Mervin Whitmore, Deputy County Surveyor, in 1952, monumented with a decayed fir post, firmly set, projecting 18 ins. above ground, from which the remains of the original bearing trees:

A decayed fir snag, size indeterminate, bears N. 34° W., 7 lks. dist., with scribe marks  $\frac{1}{4}$  S1 BT visible on open blaze.

A decayed fir snag, size indeterminate, bears S. 8° E., 52 lks. dist., no marks visible.

and bearing trees mkd. by Whitmore

A fir, 30 ins. diam., bears N. 28° W., 75 lks. dist., with healed blaze.

A fir, 26 ins. diam., bears S. 17° E., 7 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 9 W

$\frac{1}{4}$   $\frac{S 1}{S 12}$

1978

Reset fir post and set a 5 ft. steel fence post alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 34 and 35, perpetuated and recorded by Leonard Whitmore, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam., firmly set, projecting 24 ins. above ground, from which the remains of the original bearing trees:

A decayed fir snag, size indeterminate, bears S. 73 $\frac{1}{4}$ ° E., 69 lks. dist., with scribe marks 4S 35 visible on open blaze.

and bearing trees mkd. by Whitmore

An alder, 17 ins. diam., bears S. 64° E., 24 lks. dist., with scribe marks  $\frac{1}{4}$  S35 BT visible on bark.

A fir, 41 ins. diam., bears N. 36 $\frac{1}{2}$ ° W., 48 lks. dist., with healed blaze.

At the corner point