

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

Reset wood post and set a 5 ft. steel fence post
alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, perpetuated and
recorded by Leonard Whitmore, Deputy County Surveyor,
in 1972, monumented with an unmarked fir post, 2 ins.
square, firmly set, projecting 24 ins. above ground,
from which the remains of the original bearing trees:

A decayed fir snag, size indeterminate, bears
N. $46\frac{1}{2}^\circ$ E., $33\frac{1}{2}$ lks. dist., with scribe marks
S12 BT visible on open blaze.

A decayed fir snag, size indeterminate, bears
S. 24° E., 36 lks. dist., no marks visible.

and a bearing tree mkd. by Whitmore

A hemlock, 36 ins. diam., bears S. 63° E., 65
lks. dist., with scribe marks $\frac{1}{4}$ S13 BT visible
on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 4 S R 9 W
 $\frac{1}{4}$ S 12
S 13
1978

from which a new bearing tree

A fir, 24 ins. diam., bears N. $51\frac{1}{2}^\circ$ W., $42\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S12 BT.

Reset fir post and set a 5 ft. steel fence post
alongside iron post.

The cor. of secs. 1, 2, 11, and 12, perpetuated and
recorded by Mervin Whitmore, Deputy County Surveyor, in
1959, monumented with an iron pipe, 1 in. diam., firmly
set, projecting 28 ins. above ground, from which the
original bearing trees:

An alder, 17 ins. diam., bears S. 22° E., $94\frac{1}{2}$ lks.
dist., with healed blaze, and re-scribed T4S R9W
S11 BT on bark by Whitmore.

An alder, 17 ins. diam., bears S. $38\frac{3}{4}^\circ$ W., 137 lks.
dist., with scribe mark W visible on opened
blaze, and re-scribed T4S R9W S11 BT on bark
by Whitmore.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 4 S R 9 W
S 2 | S 1
S 11 | S 12
1978