Remonumentation of Certain Original Corner Points, T. 6 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree mkd. by Leonard Whitmore, Deputy County Surveyor, in 1975

A hemlock, 33 ins. diam., bears S. 41° E., 47½ lks. dist., with scribe marks ½ S10 BT visible on partially open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

from which a new bearing tree

A sawed fir stump, 27 ins. diam., bears N. 29° E., 50 lks. dist., mkd. ½ S3 BT.

The ½ sec. cor. of secs. 16 and 17, perpetuated and recorded by Leonard Whitmore, Deputy County Surveyor, in 1973, monumented with an iron pipe, ½ in. diam., firmly set, projecting 20 ins. above ground, from which the remains of the original bearing trees:

- A hemlock, 25 ins. diam., bears N. 38° E., 16 lks. dist., with scribe marks ½ visible on opened blaze. (Record, N. 35° E.)
- A hemlock snag, 8 ins. diam., bears S. 35½° W., 8 lks. dist., with scribe marks ½ S visible on opened blaze. (Record, S. 33° W.)

and bearing trees mkd. by Whitmore

- A hemlock, 22 ins. diam., bears S. 46½° E., 23 lks. dist., with fragmentary scribe marks visible on partially open blaze.
- A spruce, 32 ins. diam., bears N. 10° W., $45\frac{1}{2}$ lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Reset iron pipe alongside iron post.

The cor. of secs. 8, 9, 16, and 17, determined at record distance from the remains of the original bearing trees:

A root hole, bears N. 74° E., 67 lks. dist., with a down spruce alongside, 20 ins. diam., with scribe marks S9 BT visible on opened blaze.

135