

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

(Remonumenting corners established by Albert P. Wilson,
U. S. Deputy Surveyor, in 1890)

The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, determined at record
distance from the remains of the original bearing trees:

A hemlock snag, 17 ins. diam., bears N. $37\frac{1}{2}^{\circ}$ W.,
5 lks. dist., with scribe marks $\frac{1}{4}$ S visible on
opened blaze.

A hemlock, 22 ins. diam., bears S. 1° E., 34 lks.
dist., with healed blaze. (Record, S. $4\frac{1}{2}^{\circ}$ E.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 6 S R 10 W
 $\frac{1}{4}$ $\frac{S 10}{S 15}$
1979

from which a new bearing tree

A hemlock, 40 ins. diam., bears N. 66° W., 12 lks.
dist., mkd. $\frac{1}{4}$ S10 BT.

The cor. of secs. 3, 4, 9, and 10, determined at record
distance from the remaining original bearing trees:

A fir, 31 ins. diam., bears N. 29° E., 26 lks.
dist., with fragmentary scribe marks visible
on partially opened blaze. (Record, N. 26° E.)

A fir, 23 ins. diam., bears S. 63° E., 6 lks.
dist., with fragmentary scribe marks visible
on partially opened blaze. (Record, S. 77° E.)

A spruce, 42 ins. diam., bears N. 28° W., 61 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 6 S R 10 W
S 4 | S 3
S 9 | S 10
1979

from which a new bearing tree

A spruce, 27 ins. diam., bears S. 60° W., 76 lks.
dist., mkd. T6S R10W S9 BT.

The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, determined at record
bearing and distance from the remains of an original
bearing tree:

A sawed spruce stump, 48 ins. diam., bears
N. 20° W., 18 lks. dist., with fragmentary
scribe marks visible on partially opened blaze.