

201

Remonumentation of Certain Original Corner Points,  
T. 6 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 6 S R 10 W
S 3   S 2
S 10   S 11
1979

from which new bearing trees

A spruce, 37 ins. diam., bears N. 55½° E., 51 lks. dist., mkd. T6S R10W S2 BT.

A hemlock, 15 ins. diam., bears S. 7° E., 28 lks. dist., mkd. T6S R10W S11 BT.

A spruce, 30 ins. diam., bears N. 25° W., 23 lks. dist., mkd. T6S R10W S3 BT.

Reset iron pipe alongside iron post.

(Remonumenting corners established by Morris Wygant,  
U. S. Deputy Surveyor, in 1905)

The cor. of secs. 21, 22, 27, and 28, monumented with an iron pipe, ¾ in. diam., firmly set, projecting 30 ins. above ground, from which the remains of the original bearing trees:

A fir, 35 ins. diam., bears N. 81½° E., 52 lks. dist., with healed blaze.

A root hole, bears S. 45½° E., 97 lks. dist., with a down fir alongside, 24 ins. diam., no marks visible.

A spruce, 40 ins. diam., bears S. 22° W., 32 lks. dist., with opened blaze, no marks visible.  
(Record, fir, S. 28° W.)

A fir, 48 ins. diam., bears N. 87° W., 53 lks. dist., with fragmentary scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 10 W
S 21   S 22
S 28   S 27
1979

from which new bearing trees

A fir, 27 ins. diam., bears S. 75° E., 81½ lks. dist., mkd. T6S R10W S27 BT.

A fir, 35 ins. diam., bears N. 65° W., 85½ lks. dist., mkd. T6S R10W S21 BT.

Reset iron pipe alongside iron post.