

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

T 6 S R 10 W

 $\frac{1}{2}$
S 2 | S 1
1979

from which new bearing trees

A sawed fir stump, 25 ins. diam., bears S. 49° E.,
78 lks. dist., mkd. $\frac{1}{2}$ S1 BT.

A hemlock, 7 ins. diam., bears N. 64 $\frac{1}{2}$ ° W., 88 lks.
dist., mkd. $\frac{1}{2}$ S2 BT.

Reset iron pipe alongside iron post.

(Remonumenting a corner established by Morris Wygant,
U. S. Deputy Surveyor, in 1905)

The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, determined at record
distance from the original bearing trees:

A fir, 45 ins. diam., bears N. 49° E., 121 lks.
dist., with healed blaze. (Record, N. 46 $\frac{3}{4}$ ° E.)

A fir, 39 ins. diam., bears N. 35° W., 79 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 6 S R 10 W

 $\frac{1}{4}$
S 22 | S 23
1979

from which a new bearing tree

A fir, 18 ins. diam., bears S. 80 $\frac{1}{2}$ ° W., 14 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{2}$ S22 BT.

(Remonumenting corners established by Albert P. Wilson,
U. S. Deputy Surveyor, in 1890)

The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, perpetuated and re-
corded by Leonard Whitmore, Deputy County Surveyor, in
1963, monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly
set, projecting 28 ins. above ground, from which the
remains of the original bearing trees:

A decayed hemlock stump, size indeterminate, bears
S. 69° E., 20 lks. dist., no marks visible.

A decayed fir stump, size indeterminate, bears
S. 53° W., 17 lks. dist., with scribe marks $\frac{1}{2}$ S
visible on decayed blaze. (Record, S. 49° W.)

and bearing trees mkd. by Whitmore

A hemlock, 22 ins. diam., bears N. 68° E., 92 lks.
dist., with healed blaze.